



Estructura en aluminio



Instalación de cofres 5036



Iluminación LED integrada (opcional)

### CARACTERISTICAS

MEDIDAS		
SALIDA	LINEA MIN	LINEA MAX
1500 x 1500	1900	6000
1750 x 1750	2150	6000
2000 x 2000	2400	6000
2250 x 2250	2650	6000
2500 x 2500	3150	6000
3000 x 3000	3400	6000


Clase II  
Según norma EN13561



ABACO CLASIFICACION AL VIENTO								
3000	3500	4000	4500	5000	5500	6000	L	S
								1500
								1750
								2000
								2250
								2500
								3000

49 km/h Clase III    38 km/h Clase II    29 km/h Clase I

### INSTALACION



Incompatible con los automatismos




Al incorporar el pie telescópico, se pierde la clasificación CE

### ACCIONAMIENTO



MAQUINA  
(Max. 5000 x 3000)



MOTOR  
(Standard iO)



MOTOR  
(Radio-SIMU)

OPCIONAL

OPCIONAL

### OPCIONAL



LED  
(Brazos)



PIE TELESCÓPICO

### CERTIFICADOS



MARCA CE



TORNILLERIA



LACADO

### COLORES BASE



Blanco



Ral 1013



Ral 7016



Ral 7016  
Texturado



Bronce  
Texturado



Negro  
Texturado



Ral 8014  
Texturado



Plata  
Texturado

### COLORES STANDARD



Ral 8014



Ral 8017



Ral 8019



Ral 7035



Inox



Ral 7022



Ral 6005



Ral 6009



Ral 3005

MÁS INFORMACIÓN  
APP

